



Specification Information

OLYMPIC RANGE	
Board Material	19mm Moisture Resistant - Melamine Faced Chipboard (also known as M/R MFC)
	Meeting the requirements of BS EN 14322 & PEFC Accredited
Edging	All Panels are lipped with Matching 2mm ABS Edging Tape for added Edge Protection.
Cubicle Panels	Doors, Dividers & Pilasters are Manufactured from 19mm Moisture Resistant MFC.
Cubicle Panel Sizes	As Standard - Doors, Dividers & Pilasters are Manufactured 1800mm in Height.
	As Standard - Door Openings Range Between 580mm and 620mm. Doors are 40mm bigger allowing 20mm Overhang to both the Hinge and Clashing Side.
	As Standard - Dividers are 1500mm Deep, Larger Dividers are available.
Pre-Drilled Panels	Doors are Pre-Drilled for Locks & Hinges
	Pilasters are Pre-Drilled for Legs & Hinges
Ground Clearance	Cubicle Legs and Panels are supplied to give a Ground Clearance of 150mm
Furniture	All Cubicle Hardware is Manufactured from Aluminium - Standard SAA - (Silver Finish)
Environment	Light to Medium usage applications ~ Not suitable for Wet Areas
	Suitable for Dry Areas that may be subject to Occasional Short Term Exposure to Moisture
Usages *	Toilet Cubicles
	W/C Duct & Urinal Duct Panels.
	Vanity Duct Panels and Shadow Panels**.
<p>* The buyer is responsible for ensuring products purchased is suitable for its intended environment.</p> <p>** Shadow Panels - Must be Correctly Sealed - As per our Guidance Drawings IPS & Vanity Floor Detail.</p>	